

NPC-PHL20A

PWM Charge Controller

- Can handle up to 340/680 watts of panel power at 12/24Volts
- Positive ground charge controller (compatible with negative ground system, see instruction manual)
- Automatic 12/24V(FLD/GEL/SLD) DC detection, 12V/24V(manual set for Li), 20A rated charge current
- Automatic temperature compensation
- Smart 3 stage PWM charging (Equalization, Boost, and Float)



SPECIFICATIONS

Type	NPC-PHL20A
System voltage	12V/24V Auto
No-load Loss	8ma(12V), 12ma(24V)
Max PV Input Voltage	<55V
Rated Charge Current	20A
Max PV Input Power	340W/12V, 680W/24V
Battery Type Selection	FLD, SEL, GEL, LI
Float Charge Voltage	13.8V*n
Boost Charge Recovery Volt	13.2V*n
Over Discharge Recovery Voltage	12.6V*n
Over Discharge Voltage	11.1V*n
Operation Temperature	-25°C ~ +65°C
IP Protection	IP30
Net Weight [lbs/g]	0.44[200]
Display	LCD
Operation Altitude	≤3000M
Size [in/mm]	4.80[122] x 2.76[70] x 1.36[34.5]



702-628-7600



sales@newpowa.com



www.newpowa.com



3633 Inland Empire Blvd, Ste 600, Ontario, CA 91764